




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷: F41H 5/04, A41D 31/00	A1	(11) International Publication Number: WO 00/31494 (43) International Publication Date: 2 June 2000 (02.06.00)
(21) International Application Number: PCT/GB99/03863 (22) International Filing Date: 22 November 1999 (22.11.99) (30) Priority Data: 9825490.7 21 November 1998 (21.11.98) GB (71)(72) Applicant and Inventor: HAMLETT, Peter, Edmund [GB/GB]; Unit 2 Lumen Road, Royston, Herts SG8 7AG (GB). (74) Agent: MAGUIRE BOSS; 5 Crown Street, St. Ives, Cambridge PE17 4EB (GB).		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>

(54) Title: FLEXIBLE BODY ARMOUR**(57) Abstract**

The invention provides flexible body armour comprising a flexible carrier layer (30) and a plurality of mutually staggered layers of armour plates (10) mounted on the carrier layer such that the plates are rotatable at least to a limited degree and form a continuous protective layer. The plates may be disc-like and rotatable about their centres. The plates in each layer are preferably orientated in a plane. The plates are mounted on the carrier layer by means of rivets or studs (22).

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

5

TITLE: FLEXIBLE BODY ARMOUR

10

DESCRIPTION

15

TECHNICAL FIELD

The invention relates to flexible body armour and more particularly, but not exclusively, to body armour which is stab resistant.

20

BACKGROUND ART

One known type of flexible body armour is chain mail made of titanium. A problem with such armour is that it is not always effective against thin pointed stabbing weapons. There is also a problem of expense.

25

It is an object of the present invention to provide flexible body armour in which these problems are at least mitigated.

DISCLOSURE OF INVENTION

According to the present invention, there is provided flexible body armour comprising a plurality of superposed layers of discrete, substantially plate-like elements of resilient material mounted on a flexible carrier, in each of which layers the elements are juxtaposed edge to edge in rows and columns, the elements in each layer being staggered from those in the adjacent layer or layers such that the plurality of superposed layers forms a continuous protective layer. Preferably there are three superposed layers of discrete plate-like elements.

The plate-like elements may be made of metal or plastics, e.g. polycarbonate. Preferably the elements are made from a lightweight metal such as an alloy of aluminium. The elements may be of varying sizes, but are preferably substantially identical in size over the area of the armour. Smaller elements may however be useful for gap filling at the edges of the armour. The elements may be disc-shaped. The size may be between 10mm and 200mm in diameter and may be between 0.5mm and 20mm in thickness. The thickness may vary over the width of each plate-like element.

A substantially continuous separating layer may be provided between each layer of the elements, and the separating layer may be of a flexible material e.g. a plastics net-like material. Suitably the separating material may be of a knitted nylon net of small mesh size.

The elements may be mounted on the carrier by means of

studs or rivets. The studs or rivets may be made of metal or of plastics material. Preferably the plate-like elements are rotatable on the stud or rivet in which case each element is centrally mounted on the stud or rivet.

5 The carrier may be of any suitable flexible material, and may be of leather. A preferred material is a man-made plastics material resembling leather.

BRIEF DESCRIPTION OF DRAWINGS

10 The invention is diagrammatically illustrated by way of example in the accompanying drawings in which:-

Figure 1 is a plan view of the arrangement of plate-like elements in a lower protective layer of flexible body armour;

15 Figure 2 is a plan view of the arrangement of plate-like elements in the lower and intermediate protective layers of flexible body armour;

Figure 3 is a plan view of the arrangement of plate-like elements in a top protective layer of flexible body
20 armour;

Figure 4 is a side view of the arrangement of the three layers shown in Figures 1 to 3;

Figures 5a is a front view of flexible body armour according to the invention formed into a vest,

25 Figure 5b is a perspective view of a harness on which flexible body armour as shown in Figure 5a may be mounted, and

Figure 5c is a perspective view of a flexible body

armour formed into a waistcoat.

BEST MODES FOR CARRYING OUT THE INVENTION

In the drawings there is shown flexible body armour
5 (1) comprising three superposed layers (16,18,20) of
substantially identical disc-shaped plate-like armour
elements (10). The elements (10) are made of aluminium
alloy and are mounted on a carrier layer (30) e.g. of a
leather-like material, by means of rivets (22) supported in
10 the carrier layer and passing through a central hole (12)
in each plate-like element (10), such that each element is
rotatable at least to a limited degree and is preferably
freely rotatable on the rivet. Each element (10) is
mounted on its own individual rivet.

15 In Figure 1, there is shown a lowest or bottom layer
(16) of disc-shaped plate-like elements (10). The elements
(10) are juxtaposed edge to edge in rows and columns and
the centres (12) of the elements (10) in alternate rows are
aligned. There are many gaps (14) between the elements
20 (10).

In Figure 2, an intermediate layer (18) of the disc-
shaped plate-like elements (10) has been laid over the
lowest layer (16) of Figure 1. The layers (16, 18) are
arranged such that the elements (10) in the bottom layer
25 (16) are staggered from those in the intermediate layer
(18). The centres (12) of the elements (10) in the bottom
layer (16) are aligned with the edges of the elements (10)
in the intermediate layer. Thus, the rows of elements (10)

in the bottom layer (16) are staggered from the rows of elements (10) in the intermediate layer (18). In this way, there are fewer gaps (14) in the armour, since some of the gaps between the elements (10) in the bottom layer (16) are
5 covered by the elements (10) in the intermediate layer (18). The rivets for the intermediate layer project through the gaps (14).

In Figure 3, a top layer (20) of the disc-shaped plate-like elements (10) has been placed over the bottom
10 and intermediate layers. The layers (16, 18, 20) are arranged such that the elements (10) in each of the three layers are staggered from those in other layers, with the rivets for the top layer projecting through remaining gap (14). The top layer (20) is arranged to cover the gaps
15 (14) shown in Figure 2 and thus the plurality of superposed layers forms a continuous protective flexible layer of armour.

As shown in Figure 4, a separating layer (24) of flexible knitted nylon netting is positioned between the
20 bottom and intermediate layers of elements (10) and between the intermediate and top layers of elements (10) to prevent unintended mis-positioning of the elements (10) by interleaving when the armour flexes in use.

As shown in Figures 5a, 5b and 5c, the body armour
25 according to the invention may be made up into a stab-resistant vest (26) covering a part of the body to be protected, e.g. the chest, back, sides and shoulders. In Figure 5a, an armour vest (26) is arranged to protect the

chest and sides of the wearer and is attached to a harness (32) as shown in Figure 5b by means of releasable fastenings (34), e.g. of the Velcro (Registered Trade Mark) kind, fixed to the underside of the carrier layer (30).

5 The harness (32) comprises shoulder straps (36) attached to a waist band (38), and the vest (26) is secured to the harness (32) by corresponding Velcro (Registered Trade Mark) type fastenings (34) on the shoulder straps and on the waist band.

10 Alternatively, as shown in Figure 5c, the body armour may be formed into a waistcoat (42), with fixed back armour (40) and arranged such that the wearer's chest region can be protected with further replaceable body armour, e.g. of the kind shown in Figure 5a.

15

INDUSTRIAL APPLICABILITY

The specific embodiment thus provides flexible body armour which is effective but inexpensive to produce and which is lightweight.

CLAIMS

1. Flexible body armour comprising a flexible carrier layer and a plurality of mutually staggered layers of armour plates mounted on the carrier layer such that the
5 plates are rotatable at least to a limited degree and form a continuous protective layer.
2. Flexible body armour according to claim 1, wherein the plates are rotatable about their centres.
3. Flexible body armour according to claim 1 and claim 2,
10 wherein the plates are disc-like.
4. Flexible body armour according to any one of claims 1 to 3, wherein the plates in each layer are orientated in a plane.
5. Flexible body armour according to any preceding claim,
15 wherein the elements are juxtaposed edge to edge in rows and columns.
6. Flexible body armour according to any preceding claim, wherein the plates are of similar size and comprising three superposed layers of the plates.
- 20 7. Flexible body armour according to any preceding claim, wherein the thickness of each plate varies over the width of the plate.
8. Flexible body armour according to any preceding claim, comprising a substantially continuous flexible separating
25 layer between each layer of the elements.
9. Flexible body armour according to claim 8, wherein the or each separating layer is of plastics net-like material.
10. Flexible body armour according to any preceding claim,

comprising studs or rivets mounted on the carrier layer and on which the plates are mounted.




FIG. 1

2 / 4




FIG. 2

3 / 4




FIG. 3




FIG. 4

4 / 4




FIG. 5a




FIG. 5b




FIG. 5c

INTERNATIONAL SEARCH REPORT

Inter nal Application No

PCT/GB 99/03863

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 F41H5/04 A41D31/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 F41H A41D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 515 541 A (SACKS ET AL.) 14 May 1996 (1996-05-14)	1-5, 7-10
Y	column 2, line 66 -column 4, line 58; figures 1-7	6
Y	US 5 514 241 A (GOULD ET AL.) 7 May 1996 (1996-05-07)	6
A	column 6, line 41 - line 46; figures 7,8	1-5
A	US 4 951 689 A (JONES) 28 August 1990 (1990-08-28)	1-5, 10
	column 2, line 17 -column 3, line 1; figures 1-4	
A	DE 197 07 375 A (SCHLEGELMILCH) 27 August 1998 (1998-08-27)	3-6
	the whole document	
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

2 February 2000

Date of mailing of the international search report

10/02/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Giesen, M

INTERNATIONAL SEARCH REPORT

Inter 1al Application No
PCT/GB 99/03863

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 601 895 A (CUNNINGHAM) 11 February 1997 (1997-02-11) column 6, line 37 -column 7, line 62; figures 1-3 ----	3-6
A	WO 93 21492 A (PATCHETT) 28 October 1993 (1993-10-28) page 9, line 33 -page 10, line 3; figures 5,8B ----	4,6,7,9, 10
A	US 3 563 836 A (DUNBAR) 16 February 1971 (1971-02-16) ----	
A	GB 425 066 A (DWORACZEK) ----	
A	US 3 813 281 A (BURGESS ET AL.) 28 May 1974 (1974-05-28) -----	

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 99/03863

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5515541	A	14-05-1996	EP 0613550 A WO 9310419 A GB 2261589 A,B JP 8500424 T	07-09-1994 27-05-1993 26-05-1993 16-01-1996
US 5514241	A	07-05-1996	US 5407612 A US 5200263 A WO 9415491 A	18-04-1995 06-04-1995 21-07-1994
US 4951689	A	28-08-1990	NONE	
DE 19707375	A	27-08-1998	NONE	
US 5601895	A	11-02-1997	NONE	
WO 9321492	A	28-10-1993	AU 3902193 A ZA 9302608 A	18-11-1993 24-01-1994
US 3563836	A	16-02-1971	NONE	
GB 425066	A		BE 399955 A CH 176668 A DE 631540 C FR 767454 A	17-07-1934
US 3813281	A	28-05-1974	NONE	